


SOLID EURO CONTAINERS WITH A COUPLING SYSTEM EG VL 86/52 HG



Tight fit

The coupling system is used for those times when Euro containers have to be firmly connected to one another and not stacked. Locked and opened with a flick of the wrist, a stack of Euro containers can be turned into a compact tower that is handled like one single container.

- Strong, dependable connection
- Fast and easy locking and unlocking
- Improved stack handling



DETAILS

Outer dimensions L x W x H	80 x 60 x 52 cm	Handles long side Comprising	closed 1x EG 86/52 HG 4x EG V 86
Inner dimensions L x W x H	76.7 x 56.7 x 50.5 cm	Volume	228 liter
Usable interior height in stack	49.2 cm	Weight	7.37 kg
Stacking height	50.8 cm	Material	PP
Side design	Closed	Production information	Colour fluctuations are unavoidable due to raw material reasons
Base design	Reinforced, closed	Colour	silver grey similar RAL 7001
Coupling system design	Long side		
Handles front	closed		

Identified risks and safety information

The following potential risks have been identified when using the product:

- Material breakage due to overloading or incorrect handling with an associated risk of cuts*¹
- Risk of injury due to improper handling or heavy lifting
- Risk of slipping on uneven or wet surfaces
- Risk of crushing or pinching fingers and hands*²

Measures for minimising risk

To minimise the risks mentioned, the following safety measures should be observed:

- Always observe the maximum load limit of the product. If this is not specified in the product details, it should be evaluated independently.
- Use suitable lifting and transport equipment.
- Ensure that the product is placed on a stable and level surface.

Material and recycling information

The product is made of recyclable PP and should be disposed of in accordance with local recycling guidelines.

*¹ Appendix: Risk of cuts

Overloading or damage to the material can result in sharp edges that pose a risk of cuts. To minimise this risk, the following precautions should be taken:

- Never exceed the maximum load limit.
- Check the product regularly for signs of damage or cracks and do not use it if such defects are present.
- Wear suitable protective gloves when handling the damaged product to protect your hands from sharp edges.

*² Appendix: Crush risk

There is a risk of crushing or trapping fingers and hands when using the product, especially when stacking, folding or unfolding the product. This risk increases if the product is operated improperly or hastily. To reduce this risk, the following measures should be observed:

- Keep your hands and fingers away from the stacking, folding or collapsing mechanisms while handling the product.
- Carry out all movements slowly and in a controlled manner to prevent the product from closing unintentionally.
- If necessary, use suitable protective gloves to provide additional protection for your hands.