

AF4515T-FUW

Dino-Lite Edge



Summary

Designed for professionals in need of observing their target with different wavelengths, Dino-lite 1.3MP AF4515T-FUW digital microscope offers a 375nm UV and white light dual light source.

Overview

Dual light

Switch between white light and 375nm UV light with the click of a button

1.3 Megapixels

Thanks to the MJPEG compression, the advanced CMOS image sensor allows to transmit fluid and crisp image with resolution up to 1280x1024.

Adaptable interface

The adaptable interface provides the capability of transforming Dino-Lite into a wireless microscope when attaching with WF-20.

Automatic Magnification Reading (AMR)

Without the hassle to stop and check the magnification for doing a measurement, the AMR detects the magnification rate automatically through the software, making the measurement be a more efficient, accurate, and pleasant process.

Adjustable LED intensity

The LED intensity could be adjusted within 6 levels for providing further illumination flexibility.

Scroll Lock


The scroll lock ensures the focus knob staying at the desired focus or magnification position without worry of unintentional movement.

Interchangeable caps

The interchangeable caps provide adaptability to numerous applications with alternative lighting or object interface, such as but not limited to diffused-light, ring-light, and coaxial-light etc.

Specification

Model	AF4515T-FUW
Series	Dino-Lite Edge
Interface	USB 2.0
Resolution	2.0 Megapixel (1280 x 1024)
Magnification	20x ~ 220x
Frame Rate	15fps at 1.3MP, MJPEG 30fps at VGA, MJPEG
System Requirements	CPU: 2.5 GHz dual-core Intel Core i5 equivalent or greater RAM: 4 GB or more HD: 150 MB space available or more
Operating System	Windows 7/8/10/11 macOS 10.14 or later
Saving Format	Image: DinoCapture 2.0: BMP, PNG, TIF, JPG DinoCapture 3.0: BMP, PNG, TIF, JPG DinoXcope: PNG, JPEG Video: DinoCapture 2.0: WMV, FLV, SWF

	DinoCapture 3.0: MP4 DinoXscope: MOV
Measurement Function	Yes
Calibration Function	Yes
Microtouch	Yes
Scroll Lock	Yes
Illumination	UV Light (375nm), 4 LEDs White Light, 4 LEDs
Included Front Caps	N3C-C (Close Cap) N3C-D (Diffuser Cap) N3C-D2 (Opal Diffuser Cap) N3C-EB (Extended Open Black Cap) N3C-L (Long Cap) N3C-OB (Black Open Cap) N3C-S (Sidelight Cap) (View more front cap details)
Unit Dimension	114 mm (H) x 34 mm (D) 
Unit Weight	111 g

Optical Data Table

M	WD	FOV (x)	FOV (y)	DOF
20	60.2	19.5	15.6	2.5
30	33.5	13	10.4	1.8
40	20.9	9.8	7.8	1.5
50	13.9	7.8	6.3	

60	9.7	6.5	5.2	
70	7.1	5.6	4.5	1.0
80	5.5	4.9	3.9	
90	4.5	4.3	3.5	
100	4.1	3.9	3.1	
110	4	3.6	2.8	
120	4.1	3.3	2.6	
130	4.5	3	2.4	
140	5	2.8	2.2	
150	5.6	2.6	2.1	
160	6.3	2.4	2	
170	7.1	2.3	1.8	
180	8	2.2	1.7	
190	8.9	2.1	1.6	
200	9.9	2	1.6	
210	10.9	1.9	1.5	
220	11.9	1.8	1.4	0.1

M = magnification rate WD = working distance (without front cap) FOV = field of view
 DOF= depth of field Unit = mm

<https://www.dinolite.us>

Toll-free: 888-668-2442

Local: 310-618-9990

International: +1 310 618 9990

Sales: sales@dinolite.us

Support: support@dinolite.us

Schedule a free online demo!

<https://www.dinolite.us/meeting>