


## M8 socket to M12



|                                     |                                                                                                                           |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Product-Nr.</b>                  | 200200-21                                                                                                                 |
| <b>EAN:</b>                         | 4260556626192                                                                                                             |
| <b>Model:</b>                       | M8 Connector                                                                                                              |
| <b>Order number:</b>                | 200200-21                                                                                                                 |
| <b>Model:</b>                       | M8 Connector                                                                                                              |
| <b>Type:</b>                        | M8 socket to M12                                                                                                          |
| <b>Coding:</b>                      | A-coded                                                                                                                   |
| <b>Amount:</b>                      | 1 piece                                                                                                                   |
| <b>Suitable for:</b>                | TUBELED_25 (not TUBELED_25 RGB-W)                                                                                         |
| <b>Connection type:</b>             | screw-fastened                                                                                                            |
| <b>Material:</b>                    | Contact carrier: plastic, TPU, BK; Overlay: metal, CuZn, nickel-plated; Seal: FPM/FKM; Contacts: metal, CuZn, gold-plated |
| <b>Mechanical life:</b>             | >100 mating cycles                                                                                                        |
| <b>Ambient temperature:</b>         | -30°C -> +90 °C (-22 °F -> 194 °F)                                                                                        |
| <b>Insulation resistance (Ohm):</b> | >= 100 Mio.                                                                                                               |
| <b>Number of poles:</b>             | 3                                                                                                                         |
| <b>Handle body material:</b>        | Plastic, TPU, BK                                                                                                          |
| <b>Contact carrier material:</b>    | Plastic, TPU, BK                                                                                                          |
| <b>Cover material:</b>              | Metal, CuZn, nickel-plated                                                                                                |
| <b>Contact material:</b>            | Metal, CuZn, gold-plated                                                                                                  |
| <b>Weight (net):</b>                | 100 g (~4 oz)                                                                                                             |
| <b>Gross weight:</b>                | 100 g (~4 oz)                                                                                                             |
| <b>Markings:</b>                    | CE                                                                                                                        |
| <b>Feature:</b>                     | Non compatibile con le scatole di dimmerazione (210700-04, 210700-05, 210700-06)                                          |