




LED workplace light with gooseneck



Abstand d=50 cm
 $E_{\text{max}} = 3114 \text{ lux}$
 $E_{\text{min}} = 8584 \text{ lux}$
 $E_{\text{av}} = 516 \text{ lux}$



Product-Nr.	121012-01
EAN:	4260556623719
Model:	CENALED SPOT Flexible Arm
Order number:	121012-01
Model:	CENALED SPOT Flexible Arm
Type:	LED workplace light with gooseneck
Illuminant:	High Power LED
Power consumption:	~8,5 W
Lamp luminous flux:	1120 lm
Lamp luminous efficiency:	134 lm/W
Light distribution:	Direct
Light colour:	5000K 3-step MacAdam
Colour rendering (Ra):	>80
Supply voltage:	24V DC $\pm$ 10%
Power supply:	-
Connection (connector):	Connection cable, oil flex, with open cable ends
Degree of protection:	IP67
Class of protection:	III
Beam angle (optics):	30°
Operating temperature:	-10 °C - +50 °C (14 °F - 122 °F)
Lamps lifetime:	> 100,000 h (L90/B10)
Housing material:	aluminium (powder finished)
Cover material:	tempered glass, shatterproof
Flex arm length [A]:	500 mm (19,69")
base height:	59 mm (2,32")
Mounting:	screw-on base
Weight (net):	1660 g (~59 oz)
Gross weight:	1740 g (~61 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Yes, via push button at the light head, ON/OFF and dimming
Mounting accessories:	Magnet holder plate optional
Made in:	Germany
Feature:	universal workplace light with high protection degree