



LED surface-mounted luminaire for machines

Product-Nr.	153010-01
EAN:	4260556625416
Model:	FIELDLED EVO Surface-Mounted, M12 front-end

Order number:	153010-01
Model:	FIELDLED EVO Surface-Mounted, M12 front-end

Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	~19 W
Lamp luminous flux:	3000 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	Direct

Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85

Supply voltage:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded, end face

Degree of protection:	IP67/IP69K
Class of protection:	III

Glare control:	Microprisms
Beam angle (optics):	100°

Operating temperature:	-30 °C - +60 °C (-22 °F - 140 °F)
Storage temperature:	-30 °C - +80 °C (-22 °F - 176 °F)

Lamps lifetime:	> 100,000 h (L80/B10)
Vibration resistance:	At 10 to 55 Hz (amplitude 0.35 mm (~0,01"))

Shock resistance:	Up to 50 g (~2 oz)
Housing material:	aluminium

Cover material:	ESG (toughened tempered glass), shatterproof
Height [B] x Width [C]:	30 mm x 96 mm (~1,18" x ~3,78")

Length [A]:	280 mm (~11,02")
Weight (net):	1180 g (~42 oz)

Gross weight:	1330 g (~47 oz)
Risk group (DIN EN 62471):	Free group

Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional via accessories

Mounting accessories:	Optional; two continuous screw channels for metric screws with thread M5 on the reverse
-----------------------	---

Made in:	Germany
----------	---------

Note:	Connection Plug connector M12 A-coded, front side
-------	---

