




LED surface-mounted luminaire



Abstand d=100 cm

 $E_{\text{min}} = 162 \text{ lux}$
 $E_{\text{max}} = 218 \text{ lux}$
 $E_{\text{avg}} = 98 \text{ lux}$


Product-Nr.	111010-01
EAN:	4260556624006
Model:	LEANLED II Clear
Order number:	111010-01
Model:	LEANLED II Clear
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~4,3 W
Lamp luminous flux:	750 lm
Lamp luminous efficiency:	~173 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP54
Class of protection:	III
Beam angle (optics):	120°
Operating temperature:	-10 °C - +60 °C (14 °F - 140 °F)
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonat, clear, shatterproof
Height [B] x Width [C]:	31 mm x 26 mm (~1,22" x ~1,02")
Length [A]:	180 mm (~7,09")
Weight (net):	210 g (~7 oz)
Gross weight:	250 g (~9 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Dimmable:	Optional via accessories
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope
Made in:	Germany