




LED surface-mounted luminaire



Abstand d=100 cm

E_{min} = 476 luxE_{max} = 633 luxE_{avg} = 300 lux

Product-Nr. 111010-04

EAN: 4260556624037

Model: LEANLED II Clear

Order number: 111010-04

Model: LEANLED II Clear

Type: LED surface-mounted luminaire

Illuminant: SMD LED

Power consumption: ~13 W

Lamp luminous flux: 2250 lm

Lamp luminous efficiency: ~173 lm/W

Light distribution: Direct

Light colour: 5700K 3-step MacAdam

Colour rendering (Ra): >85

Supply voltage: 24V DC ± 10%

Connection (connector): M12 A-coded

Degree of protection: IP54

Class of protection: III

Beam angle (optics): 120°

Operating temperature: -10 °C - +60 °C (14 °F - 140 °F)

Lamps lifetime: > 100,000 h (L80/B10)

Housing material: aluminium

Cover material: Polycarbonat, clear, shatterproof

Height [B] x Width [C]: 31 mm x 26 mm (~1,22" x ~1,02")

Length [A]: 520 mm (~20,47")

Weight (net): 440 g (~16 oz)

Gross weight: 500 g (~18 oz)

Risk group (DIN EN 62471): Free group

Markings: CE, UKCA, ETL Listed (5003529), D mark

Dimmable: Optional via accessories

Mounting accessories: 2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope

Made in: Germany