


LED surface-mounted luminaire for machines



Product-Nr.	111010-57
EAN:	4260556627946
Model:	LEANLED II Basic-Line Opal White
Order number:	111010-57
Model:	LEANLED II Basic-Line Opal White
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	34,6 W
Lamp luminous flux:	5355 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>80
Supply voltage:	24V DC *
Power supply:	External
Connection (connector):	M12 A-coded
Number of poles:	3
Degree of protection:	IP54
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	120°
Operating temperature:	0 °C - +45 °C (32 °F - 113 °F)
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonat
Height [B] x Width [C]:	31 mm x 26 mm (~1,22" x ~1,02")
Length [A]:	1520 mm (~59,84")
Weight (net):	950 g (~34 oz)
Gross weight:	1450 g (~51 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Dimmable:	No
Mounting accessories:	Including swivel and fixed bracket
Made in:	Germany
Note:	In case of an undervoltage supply (< 24V DC), the luminous flux is reduced
cascadable:	No