




pofiled light with t-slot backsided



Product-Nr.	150714-03
EAN:	4260556623870
Model:	PROFILED AC
Order number:	150714-03
Model:	PROFILED AC
Type:	pofiled light with t-slot backsided
Illuminant:	SMD LED
Total output incl. driver:	~27 W
Power consumption:	~23 W
Lamp luminous flux:	3674 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	120-277V AC $\pm$ 10%, 50-60 Hz
Power supply:	Integrated
Connection (connector):	3 m (~9,84 ft.) connection cable with power plug
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-10 °C - +45 °C (14 °F - 113 °F)
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (~2,56" x ~1,77")
Length [A]:	1000 mm (~39,37")
Weight (net):	2440 g (~86 oz)
Gross weight:	3140 g (~111 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Mounting accessories:	Optional
Made in:	Germany
Feature:	universal light