




profiled light with t-slot backsided



|                                   |                                      |
|-----------------------------------|--------------------------------------|
| <b>Product-Nr.</b>                | 150314-08                            |
| <b>EAN:</b>                       | 4260556626420                        |
| <b>Model:</b>                     | PROFILED AC                          |
| <b>Order number:</b>              | 150314-08                            |
| <b>Model:</b>                     | PROFILED AC                          |
| <b>Type:</b>                      | profiled light with t-slot backsided |
| <b>Illuminant:</b>                | SMD LED                              |
| <b>Total output incl. driver:</b> | ~14 W                                |
| <b>Power consumption:</b>         | ~11 W                                |
| <b>Lamp luminous flux:</b>        | 1670 lm                              |
| <b>Lamp luminous efficiency:</b>  | ~155 lm/W                            |
| <b>Light distribution:</b>        | Direct                               |
| <b>Light colour:</b>              | 5700K 3-step MacAdam                 |
| <b>Colour rendering (Ra):</b>     | >85                                  |
| <b>Supply voltage:</b>            | 120-277V AC $\pm$ 10%, 50-60 Hz      |
| <b>Power supply:</b>              | Integrated                           |
| <b>Connection (connector):</b>    | Wieland GST18                        |
| <b>Degree of protection:</b>      | IP40                                 |
| <b>Class of protection:</b>       | I                                    |
| <b>Glare control:</b>             | Microprisms                          |
| <b>Beam angle (optics):</b>       | 100°                                 |
| <b>Operating temperature:</b>     | -10 °C - +45 °C (14 °F - 113 °F)     |
| <b>Lamps lifetime:</b>            | > 100,000 h (L80/B10)                |
| <b>Housing material:</b>          | aluminium                            |
| <b>Cover material:</b>            | plastics                             |
| <b>Height [B] x Width [C]:</b>    | 65 mm x 45 mm (~2,56" x ~1,77")      |
| <b>Length [A]:</b>                | 500 mm (~19,69")                     |
| <b>Weight (net):</b>              | 1450 g (~51 oz)                      |
| <b>Gross weight:</b>              | 1800 g (~63 oz)                      |
| <b>Risk group (DIN EN 62471):</b> | Free group                           |
| <b>Markings:</b>                  | CE, UKCA                             |
| <b>Dimmable:</b>                  | Internal dimmer control              |
| <b>Mounting accessories:</b>      | Optional                             |
| <b>Made in:</b>                   | Germany                              |
| <b>Feature:</b>                   | universal light, dimmable            |