






profiled light with t-slot backsided



Abstand d=100 cm

E_{min} = 708 lux
 E_{max} = 980 lux
 E_{m} = 392 lux



Product-Nr. 150614-07

EAN: 4260556626437

Model: PROFILED AC

Order number: 150614-07

Model: PROFILED AC

Type: profiled light with t-slot backsided

Illuminant: SMD LED

Total output incl. driver: ~24 W

Power consumption: ~21 W

Lamp luminous flux: 3340 lm

Lamp luminous efficiency: ~155 lm/W

Light distribution: Direct

Light colour: 5700K 3-step MacAdam

Colour rendering (Ra): >85

Supply voltage: 120-277V AC $\pm$ 10%, 50-60 Hz

Power supply: Integrated

Connection (connector): Wieland GST18

Degree of protection: IP40

Class of protection: I

Glare control: Microprisms

Beam angle (optics): 100°

Operating temperature: -10 °C - +45 °C (14 °F - 113 °F)

Lamps lifetime: > 100,000 h (L80/B10)

Housing material: aluminium

Cover material: plastics

Height [B] x Width [C]: 65 mm x 45 mm (~2,56" x ~1,77")

Length [A]: 900 mm (~35,43")

Weight (net): 1950 g (~69 oz)

Gross weight: 2650 g (~93 oz)

Risk group (DIN EN 62471): Free group

Markings: CE, UKCA

Mounting accessories: Optional

Made in: Germany

Feature: universal light