



Surface-mounted device with attachment via an elongated hole



Product-Nr.	210700-05
EAN:	4260556625409
Model:	LED2WORK DIMMbox
Order number:	210700-05
Model:	LED2WORK DIMMbox
Type:	Surface-mounted device with attachment via an elongated hole
Power:	96 W
Input/Output Voltage:	24V DC
Current load max.:	4000 mA
Assignment of PIN1 input / output:	24V DC / -
Assignment of PIN2 input / output:	digital input / -
Assignment of PIN3 input / output:	GND / GND
Assignment of PIN4 input / output:	digital input / +24V out
Assignment of PIN5 input / output:	digital input / -
Output voltage:	24V DC
Material:	Casing: Plastic
Dimming:	Via external control
Input/Output Connection:	M12A plug / M12A socket
ON/OFF switch:	Yes
Degree of protection:	IP54
Operating temperature:	-20 °C - +50 °C (-4 °F - 122 °F)
Storage temperature:	-20 °C - +80 °C (-4 °F - 176 °F)
Dimensions (mm):	122 mm x 33 mm x 29 mm (~4,8" x ~1,3" x ~1,14")
Weight (net):	100 g (~4 oz)
Gross weight:	150 g (~5 oz)
Markings:	CE, UKCA
PWM frequency:	~4kHz
Feature:	DIMMbox is controlled via an external controller, e.g. PLC