


PIN 3 GND
PIN 4 V DC



IP67 power source, metal housing, input: open ends, output: M12 socket, cable protection: flexible metal protection hose

Product-Nr.	210100-06
EAN:	4260556622071
Model:	Constant Voltage Power Supply
Order number:	210100-06
Model:	Constant Voltage Power Supply
Type:	IP67 power source, metal housing, input: open ends, output: M12 socket, cable protection: flexible metal protection hose
Cable length:	Input: ~0.3 m (~0.98 ft.) with open ends; output ~0.3 m (~0.98 ft.) with M12-A
Ambient temperature:	-40°C -> +80 °C (-40 °F -> 176 °F)
Nominal output voltage:	24V DC
Max. output power:	60 W
Output current:	2500 mA
Voltage range:	90...305V AC
Input frequency:	47...63 Hz
Max. input current (230 V AC):	320 mA ± 1%
Max. Input current (115 V AC):	640 mA ± 1%
Output voltage setting range:	22...27V DC
Overvoltage protection:	28...34V DC
Connection to a light:	M12 socket, A-coded
Number of poles:	4
Efficiency at full load:	89,5 %
P no:	<0,5 W
Degree of protection:	IP67
Dimensions (mm):	171 mm x 61,5 mm x 36,8 mm (~6,73" x ~2,42" x ~1,45")
Overtemperature protection:	95 °C ± 10 °C
Humidity during operation:	20...95% (non-condensing)
Weight (net):	1100 g (~39 oz)
Gross weight:	1200 g (~42 oz)
Markings:	aktive PFC, IP65, IP67, ICC, CB, CE, UKCA, UL8750 Type HL
Dimmable:	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
Protective devices:	short circuit protection, overload protection, overvoltage protection, overtemperature protection
Feature:	High degree of protection