






LED system light



Abstand d=100 cm

E_{min} = 1226 luxE_{max} = 1583 luxE_{avg} = 759 lux

Product-Nr.	155220-02
EAN:	4260556627632
Model:	SYSTEMLED EVO - ECO Neutral White

Order number:	155220-02
Model:	SYSTEMLED EVO - ECO Neutral White

Type:	LED system light
Illuminant:	SMD LED

Total output incl. driver:	~32 W
-----------------------------------	-------

Power consumption:	~28,75 W
---------------------------	----------

Lamp luminous flux:	4975 lm
----------------------------	---------

Lamp luminous efficiency:	173 lm/W
----------------------------------	----------

Light distribution:	Direct
----------------------------	--------

Light colour:	4000K 3-step MacAdam
----------------------	----------------------

R9:	90
------------	----

Colour rendering (Ra):	>90 (typ. 95)
-------------------------------	---------------

UGR:	<22
-------------	-----

Supply voltage:	120-277V AC ± 10%, 50-60 Hz
------------------------	-----------------------------

Power supply:	Integrated
----------------------	------------

Connection (connector):	Wieland GST18
--------------------------------	---------------

Degree of protection:	IP40
------------------------------	------

Class of protection:	I
-----------------------------	---

Glare control:	Microprisms
-----------------------	-------------

Beam angle (optics):	90°
-----------------------------	-----

Operating temperature:	-10 °C - +50 °C (14 °F - 122 °F)
-------------------------------	----------------------------------

Storage temperature:	-20 °C - +80 °C (-4 °F - 176 °F)
-----------------------------	----------------------------------

Lamps lifetime:	> 100,000 h (L80/B10)
------------------------	-----------------------

Housing material:	aluminum and PMMA
--------------------------	-------------------

Height [B] x Width [C]:	48 mm x 139 mm (~1,89" x ~5,47")
--------------------------------	----------------------------------

Length [A]:	1120 mm (~44,09")
--------------------	-------------------

Mounting:	T-slot rear (8 mm)
------------------	--------------------

Weight (net):	3100 g (~109 oz)
----------------------	------------------

Gross weight:	3960 g (~140 oz)
----------------------	------------------

Risk group (DIN EN 62471):	Free group
-----------------------------------	------------

Markings:	CE, UKCA
------------------	----------

Dimmable:	Optional via accessories
------------------	--------------------------

Mounting accessories:	Optional
------------------------------	----------

Made in:	Germany
-----------------	---------