



LED system light

Product-Nr.	155420-02
EAN:	4260556627656
Model:	SYSTEMLED EVO - ECO Neutral White

Order number:	155420-02
Model:	SYSTEMLED EVO - ECO Neutral White

Type: LED system light

Illuminant: SMD LED

Total output incl. driver: ~51 W

Power consumption: ~46 W

Lamp luminous flux: 7960 lm

Lamp luminous efficiency: 173 lm/W

Light distribution: Direct

Light colour: 4000K 3-step MacAdam

R9: 90

Colour rendering (Ra): >90 (typ. 95)

UGR: <22

Supply voltage: 120-277V AC $\pm$ 10%, 50-60 Hz

Power supply: Integrated

Connection (connector): Wieland GST18

Degree of protection: IP40

Class of protection: I

Glare control: Microprisms

Beam angle (optics): 90°

Operating temperature: -10 °C - +50 °C (14 °F - 122 °F)

Storage temperature: -20 °C - +80 °C (-4 °F - 176 °F)

Lamps lifetime: > 100,000 h (L80/B10)

Housing material: aluminum and PMMA

Height [B] x Width [C]: 48 mm x 139 mm (~1,89" x ~5,47")

Length [A]: 1782 mm (~70,16")

Mounting: T-slot rear (8 mm)

Weight (net): 4700 g (~166 oz)

Gross weight: 6580 g (~232 oz)


Risk group (DIN EN 62471): Free group

Markings: CE, UKCA

Dimmable: Optional via accessories

Mounting accessories: Optional

Made in: Germany



Abstand d=100 cm
 E_{max} = 1655 lux
 E_{min} = 2027 lux
 E_{avg} = 1149 lux

