




LED system light



Abstand d=100 cm

E_{max} = 543 luxE_{min} = 739 luxE_{avg} = 308 lux

Product-Nr.	155020-02
EAN:	4260556627618
Model:	SYSTEMLED EVO - ECO Neutral White

Order number:	155020-02
Model:	SYSTEMLED EVO - ECO Neutral White

Type:	LED system light
Illuminant:	SMD LED

Total output incl. driver:	~13 W
----------------------------	-------

Power consumption:	~11,5 W
--------------------	---------

Lamp luminous flux:	1990 lm
---------------------	---------

Lamp luminous efficiency:	173 lm/W
---------------------------	----------

Light distribution:	Direct
---------------------	--------

Light colour:	4000K 3-step MacAdam
---------------	----------------------

R9:	90
-----	----

Colour rendering (Ra):	>90 (typ. 95)
------------------------	---------------

UGR:	<22
------	-----

Supply voltage:	120-277V AC ± 10%, 50-60 Hz
-----------------	-----------------------------

Power supply:	Integrated
---------------	------------

Connection (connector):	Wieland GST18
-------------------------	---------------

Degree of protection:	IP40
-----------------------	------

Class of protection:	I
----------------------	---

Glare control:	Microprisms
----------------	-------------

Beam angle (optics):	90°
----------------------	-----

Operating temperature:	-10 °C - +50 °C (14 °F - 122 °F)
------------------------	----------------------------------

Storage temperature:	-20 °C - +80 °C (-4 °F - 176 °F)
----------------------	----------------------------------

Lamps lifetime:	> 100,000 h (L80/B10)
-----------------	-----------------------

Housing material:	aluminum and PMMA
-------------------	-------------------

Height [B] x Width [C]:	48 mm x 139 mm (~1,89" x ~5,47")
-------------------------	----------------------------------

Length [A]:	472 mm (~18,58")
-------------	------------------

Mounting:	T-slot rear (8 mm)
-----------	--------------------

Weight (net):	1500 g (~53 oz)
---------------	-----------------

Gross weight:	2080 g (~73 oz)
---------------	-----------------

Risk group (DIN EN 62471):	Free group
----------------------------	------------

Markings:	CE, UKCA
-----------	----------

Dimmable:	Optional via accessories
-----------	--------------------------

Mounting accessories:	Optional
-----------------------	----------

Made in:	Germany
----------	---------