




LED system light



Abstand d=100 cm

E_{max}= 543 luxE_{min}= 739 luxE_{avg}= 308 lux

Product-Nr.	155020-04
EAN:	4260556627977
Model:	SYSTEMLED EVO PIR - ECO Neutral White
Order number:	155020-04
Model:	SYSTEMLED EVO PIR - ECO Neutral White
Type:	LED system light
Illuminant:	SMD LED
Total output incl. driver:	~13 W
Power consumption:	~12 W
Lamp luminous flux:	1990 lm
Lamp luminous efficiency:	173 lm/W
Light distribution:	Direct
Light colour:	4000K3-step MacAdam
R9:	90
Colour rendering (Ra):	>90 (typ. 95)
UGR:	<22
Dimming:	Via external control; On / Off via motion activation (PIR)
Supply voltage:	120-277V AC ± 10%, 50-60 Hz
Power supply:	Integrated
Connection (connector):	Wieland GST18
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	90°
Operating temperature:	-10 °C - +50 °C (14 °F - 122 °F)
Storage temperature:	-20 °C - +80 °C (-4 °F - 176 °F)
Lamps lifetime:	> 100.000 h (L80/B10)
Housing material:	aluminum and PMMA
Height [B] x Width [C]:	48 mm x 139 mm (~1,89" x ~5,47")
Length [A]:	472 mm (~18,58")
Mounting:	T-nut, rear side (slot 8)
Weight (net):	1500 g (~53 oz)
Gross weight:	2080 g (~73 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Dimmable:	Optional via accessories
Mounting accessories:	Optional
Made in:	Germany