







LED system light



Abstand d=100 cm
 $E_{\text{max}} = 2055 \text{ lux}$
 $E_{\text{min}} = 2652 \text{ lux}$
 $E_{\text{avg}} = 1272 \text{ lux}$



Product-Nr.	155210-01
EAN:	4260556627076
Model:	SYSTEMLED EVO - POWER Daylight White

Order number:	155210-01
Model:	SYSTEMLED EVO - POWER Daylight White

Type:	LED system light
Illuminant:	SMD LED

Total output incl. driver:	~51 W
Power consumption:	~45,625 W

Lamp luminous flux:	8125 lm
Lamp luminous efficiency:	184 lm/W

Light distribution:	Direct
Light colour:	5700K 3-step MacAdam

R9:	90
Colour rendering (Ra):	>90 (typ. 95)

UGR:	<22
Supply voltage:	120-277V AC $\pm$ 10%, 50-60 Hz

Power supply:	Integrated
Connection (connector):	Wieland GST18

Degree of protection:	IP40
Class of protection:	I

Glare control:	Microprisms
Beam angle (optics):	90°

Operating temperature:	-10 °C - +50 °C (14 °F - 122 °F)
Storage temperature:	-20 °C - +80 °C (-4 °F - 176 °F)

Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminum and PMMA

Height [B] x Width [C]:	48 mm x 139 mm (~1,89" x ~5,47")
Length [A]:	1120 mm (~44,09")

Mounting:	T-slot rear (8 mm)
Weight (net):	3100 g (~109 oz)

Gross weight:	3960 g (~140 oz)
Risk group (DIN EN 62471):	Free group

Markings:	CE, UKCA
Dimmable:	Optional via accessories

Mounting accessories:	Optional
Made in:	Germany

Feature:	externally dimmable/switchable
-----------------	--------------------------------