# LED surface-mounted light



| | |
|---|---|
| **Product-Nr.** | 154390-01 |
| **EAN:** | 4260556626154 |
| **Model:** | TUBELED_25 RGB-W |










| | |
|---|---|
| Order number: | 154390-01 |
| Model: | TUBELED_25 RGB-W |
| Type: | LED surface-mounted light |
| Illuminant: | SMD RGB-W Cluster LED |
| Power consumption white: | ~14,4 W |
| White lamp luminous flux: | 2304 lm |
| Lamp luminous efficiency: | ~159 lm/W |
| Power consumption RED: | ~4,3 W |
| Lamp luminous flux RED: | 276 lm |
| Power consumption GREEN: | ~2,9 W |
| Lamp luminous flux GREEN: | 504 lm |
| Power consumption BLUE: | ~4,3 W |
| Lamp luminous flux BLUE: | 168 lm |
| Light distribution: | Direct |
| Light colour white: | 5000K 3-step MacAdam |
| Colour rendering WHITE (Ra): | >85 |
| Supply voltage: | 24 V DC -10 %+7 % (RGB) – 24 V DC ±10 % (W) |
| Connection (connector): | M8 B-coded |
| Degree of protection: | IP67 |
| Class of protection: | III |
| Glare control: | diffused safety glass |
| Beam angle (optics): | 100° |
| Operating temperature: | -30 °C - +55 °C (-22 °F - 131 °F) |
| Storage temperature: | -30 °C - +80 °C (-22 °F - 176 °F) |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Vibration resistance: | At 10 to 55 Hz (amplitude 0.35 mm (~0,01“)) |
| Shock resistance: | Up to 50 g (~2 oz) |
| Housing material: | aluminium |
| Cover material: | tempered glass, shatterproof |
| Height [B] x Width [C]: | ~23 mm x ~28 mm (~0,91“ x ~1,1“) |
| Length [A]: | 540 mm (~21,26“) |
| Weight (net): | 50 g (~2 oz) |
| Gross weight: | 550 g (~19 oz) |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | option external, PWM |
| Mounting accessories: | Optional |
| Made in: | Germany |
| Feature: | RGB-W: Illumination and beacon in one light; connection |



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com