LED surface-mounted light

Product-Nr.	118390-01
EAN:	4260556623610
Model:	TUBELED_40 II RGB-W Power

Darstellbares Farbspektrum /
Displayable colour spectrum

Mischfarben werden mit der Ansteuerung mehrerer Eingänge gleichzeitig erreicht. /
Mixed colours will be achieved with the control of multiple inputs simultaneously.



Order number:	118390-01
Model:	TUBELED_40 II RGB-W Power
Type:	LED surface-mounted light
Illuminant:	SMD RGB-W Cluster LED
Power consumption white:	~19 W
White lamp luminous flux:	2430 lm
Lamp luminous efficiency:	~126 lm/W
Power consumption RED:	~18 W
Lamp luminous flux RED:	480 lm
Power consumption GREEN:	~5 W
Lamp luminous flux GREEN:	690 lm
Power consumption BLUE:	~18 W
Lamp luminous flux BLUE:	300 lm
Light distribution:	Light Forming Technolology
Light colour white:	5600K 3-step MacAdam
Colour rendering WHITE (Ra):	>80
Supply voltage:	24 V DC -10 %+7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector):	M12 A-coded
Number of poles:	5
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-30 °C - +60 °C (-22 °F - 140 °F)
Storage temperature:	-30 °C - +80 °C (-22 °F - 176 °F)
Lamps lifetime:	> 100,000 h (L80/B10)
Vibration resistance:	At 10 to 55 Hz (amplitude 0.35 mm (~0,01“))
Shock resistance:	Up to 50 g (~2 oz)
Housing material:	aluminium
Cover material:	tempered glass, shatterproof
Height [B] x Width [C]:	29 mm x 40 mm (~1,14“ x ~1,57“)
Length [A]:	540 mm (~21,26“)
Weight (net):	650 g (~23 oz)
Gross weight:	900 g (~32 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Mounting accessories:	Optional
Made in:	Germany
Feature:	RGB-W: Illumination and beacon in one light

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com