



Product-Nr.	120910-02
EAN:	4260556624792
Model:	UNILED II Articulated Arm
Order number:	120910-02
Model:	UNILED II Articulated Arm
Type:	LED adjustable arm light
Illuminant:	SMD LED
Power consumption:	~14,5 W
Lamp luminous flux:	2668 lm
Lamp luminous efficiency:	~184 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>90
Supply voltage:	24V DC ± 10%
Power supply:	Included external PSU 100-240V AC
Connection (connector):	M12 A-coded
Connected load PSU:	100-240V AC
Connection PSU:	EURO plug to M12 connector
Degree of protection:	IP40
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-10 °C - +60 °C (14 °F - 140 °F)
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium / plastics
Cover material:	plastic soft
Head width [A]:	380 mm (~14,96")
Length articulated arms:	1x 400 mm (~15,75"), 1x 250 mm (~9,84")
Weight (net):	2900 g (~102 oz)
Gross weight:	3550 g (~125 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Dimmable:	Internal dimmer with memory function
Mounting accessories:	Included table clamp
Made in:	Germany
Feature:	dimmable, mid-level luminaire head width and shortened forearm