




LED adjustable arm light



Product-Nr.	120900-01
EAN:	4260556624808
Model:	UNILED II Articulated Arm TW
Order number:	120900-01
Model:	UNILED II Articulated Arm TW
Type:	LED adjustable arm light
Illuminant:	SUNlike LED
Power consumption:	~20 W
Lamp luminous flux:	1582 lm (6500 K) / 1468 lm (3000 K)
Lamp luminous efficiency:	~98 lm/W (6500K) / ~91 lm/W (3000K)
Light distribution:	Direct
Light colour:	warm white (3,000 K) up to daylight white (6,500 K)
Colour rendering (Ra):	>90/98
Scope of delivery:	luminaire and additional luminaire holder 210200-11
Supply voltage:	24V DC $\pm$ 10%
Power supply:	Included external PSU 100-240V AC
Connection (connector):	M12 A-coded
Connected load PSU:	100-240V AC
Connection PSU:	EURO plug to M12 connector
Degree of protection:	IP40
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-10 °C - +60 °C (14 °F - 140 °F)
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium / plastics
Cover material:	plastic soft
Head width [A]:	380 mm (~14,96")
Length articulated arms:	1x 400 mm, 1x 250 mm
Weight (net):	3220 g (~114 oz)
Gross weight:	3870 g (~137 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA
Mounting accessories:	Included table clamp
Made in:	Germany
Feature:	TUNABLE WHITE: very high colour rendering, continuously adjustable light colour from 3000 K up to 6500 K