



LED Ring Light UV and IR

RL2 UV/IR

**MADE
IN
GERMANY**

- Homogeneous illumination in the entire working range
- Perfect incident light for applications with cameras and lenses in machine vision
- Flicker-free lighting thanks to optimized electronic
- Brightness adjustable from 0 to 100%
- Various light colors and color temperatures available
- Variable clamping diameter, adaptable with reducing rings
- Solid aluminium housing in modern design



Technical Data

Number of LEDs	24
Brightness control	sensitive adjusting 0 - 100% with memory function
Power consumption	approx. 5 W
Input power supply	100 - 240 V AC, 50/60 Hz
Output power supply	24 V DC, 1 A
Height	25 mm
Outer diameter	58 mm
Inner diameter	35 mm (RL2-25), 38,5 mm (RL2-50)
Clamping diameter	max. 40 mm
Inner thread	M35,5 × 0,5 (RL2-25), M39 × 0,5 (RL2-50)
Length supply line	0,85 m
Length power cord	1,40 m
Material	anodized aluminium
Color	titanium
Weight	approx. 60 g
Dimensions control unit (l × w × h)	78 mm × 38 mm × 21 mm

Versions

100-010653	RL2-25 UV365	UV (365 nm), working distance 15 mm - 50 mm (optimal 25 mm)
100-010652	RL2-25 UV375	UV (375 nm), working distance 15 mm - 50 mm (optimal 25 mm)
100-010651	RL2-25 UV405	UV (405 nm), working distance 15 mm - 50 mm (optimal 25 mm)
100-010654	RL2-25 IR880	IR (880 nm), working distance 15 mm - 50 mm (optimal 25 mm)
100-010661	RL2-50 UV365	UV (365 nm), working distance 30 mm - 150 mm (optimal 50 mm)
100-010660	RL2-50 UV375	UV (375 nm), working distance 30 mm - 150 mm (optimal 50 mm)
100-010659	RL2-50 UV405	UV (405 nm), working distance 30 mm - 150 mm (optimal 50 mm)
100-010662	RL2-50 IR880	IR (880 nm), working distance 30 mm - 150 mm (optimal 50 mm)

Accessories

100-010713	Reducing ring	40 mm → 28 mm
100-009229	Reducing ring	40 mm → 30 mm
100-009230	Reducing ring	40 mm → 32 mm
100-009238	Reducing ring	40 mm → 34 mm
100-010712	Reducing ring	40 mm → 36 mm
100-010711	Reducing ring	40 mm → 38 mm