



Ring Light RL40

**MADE
IN
GERMANY**

- “Next Gen” LED High Power Ring Lights
- Particularly High Color Reproduction (CRI typ 97)
- Day Light Grade Lighting (5.600 K)
- Outstanding Brightness
- SMD-Technology
- Perfect for Polarisation Applications
- Brightness adjustable from 0 to 100%



Technical Data

Number of LEDs	8
Color rendering index (CRI)	≥ 95
LED life span	54.000 h (L70, according to manufacturer)
Brightness control	sensitive adjusting 0 - 100% with memory function
Power consumption	approx. 6 W
Input power supply	100 - 240 V AC, 50/60 Hz
Output power supply	24 V DC, 1 A
Height	25,1 mm
Outer diameter	58 mm
Inner diameter	30 mm
Clamping diameter	max. 40 mm
Inner thread	M30,5 × 0,5
Length supply line	0,85 m
Length power cord	1,40 m
Material	anodized aluminium
Color	black
Weight	approx. 125 g
Dimensions control unit (l × w × h)	78 mm × 38 mm × 21 mm

Versions

100-012211	RL40-35 PW	pure white (5.600 K), working distance 35 mm, clamping diameter max. 40 mm
100-012231	RL40-35 NW	natural white (4.000 K), working distance 35 mm, clamping diameter max. 40 mm
100-012180	RL40-120 PW	pure white (5.600 K), working distance 120 mm, clamping diameter max. 40 mm
100-012230	RL40-120 NW	natural white (4.000 K), working distance 120 mm, clamping diameter max. 40 mm

Accessories

100-012329	Diffuser Disc	for RL40-35 Series
100-010713	Reducing ring	40 mm → 28 mm
100-009229	Reducing ring	40 mm → 30 mm
100-009230	Reducing ring	40 mm → 32 mm
100-009238	Reducing ring	40 mm → 34 mm
100-010712	Reducing ring	40 mm → 36 mm
100-010711	Reducing ring	40 mm → 38 mm