



Ring Light UV and IR

RL40-UV

MADE
IN
GERMANY

- “Next Gen” LED High Power Ring Lights
- UV-Lights in three different Wave Lengths
- Outstanding Brightness
- SMD-Technology
- Brightness adjustable from 0 to 100%



Technical Data

Number of LEDs	8
Brightness control	sensitive adjusting 0 - 100% with memory function
Power consumption	approx. 6 W
Input power supply	100 - 240 V AC, 50/60 Hz
Output power supply	24 V DC, 1 A
Height	25,1 mm
Outer diameter	58 mm
Inner diameter	30 mm
Clamping diameter	max. 40 mm
Inner thread	M30,5 × 0,5
Length supply line	0,85 m
Length power cord	1,40 m
Material	anodized aluminium
Color	black
Weight	approx. 125 g
Dimensions control unit (l × w × h)	78 mm × 38 mm × 21 mm

Versions

100-012296	RL40-35 UV395	UV (395 nm), working distance 35 mm, clamping diameter max. 40 mm
100-012292	RL40-35 UV385	UV (385 nm), working distance 35 mm, clamping diameter max. 40 mm
100-012071	RL40-35 UV365	UV (365 nm), working distance 35 mm, clamping diameter max. 40 mm
100-012297	RL40-120 UV395	UV (395 nm), working distance 120 mm, clamping diameter max. 40 mm
100-012293	RL40-120 UV385	UV (385 nm), working distance 120 mm, clamping diameter max. 40 mm
100-012240	RL40-120 UV365	UV (365 nm), working distance 120 mm, clamping diameter max. 40 mm

Accessories

100-010214	UV-protective goggles	scratch resist, with clear glasses
100-010217	UV-protective goggles	scratch resist, with grey glasses
100-010713	Reducing ring	40 mm → 28 mm
100-009229	Reducing ring	40 mm → 30 mm
100-009230	Reducing ring	40 mm → 32 mm
100-009238	Reducing ring	40 mm → 34 mm
100-010712	Reducing ring	40 mm → 36 mm
100-010711	Reducing ring	40 mm → 38 mm