

Bracket 60x60, ESD, Slot 8/10, Die-Cast Aluminum - Bosch Rexroth 3842523551

Item no. BRR-3842523551

Manufacturer Bosch Rexroth

The 60x60 bracket joins aluminum profiles at a right angle and fits slot 8 and slot 10. It is made of vibratory-ground die-cast aluminum, is ESD-capable and ships as a set complete with fastening material. Ideal for stable profile connections in machine, frame and fixture construction.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **Germany**

HS-Code **83024900**

Weight **0.16 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The 60x60 bracket from Bosch Rexroth joins aluminum profiles at a right angle and is designed for machine, frame and fixture construction. It fits profiles with slot 8 and slot 10 and is supplied as a set complete with the required fastening material.

- Die-cast aluminum, vibratory ground, for load-bearing joints with a bending moment up to 370 Nm
- ESD-capable for applications with discharge requirements
- Fastening material included in the scope of delivery

TECHNICAL DATA

Attribute	Value
Profile slot	8, 10
Dimensions	60x60
ESD	yes
Bending moment 1	320 Nm
Bending moment 2	370 Nm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Attribute	Value
Torsional moment	110 Nm
Material	Die-cast aluminum, vibratory ground
Material information	Bracket: die-cast aluminum, vibratory ground; Fastening material: steel, galvanized
Fastening material	4x cylinder head screw DIN7984-M6x14, 4x T-nut slot 8 M6, 1x T-bolt M8x20, 1x flange nut M8
Fastening material included	yes
Scope of delivery	incl. fastening material (FS), bracket (standard)
Recommended accessories	Intermediate element for 10 mm slot (3842523537), cover cap for bracket 60x60 signal gray (3842548852), cover cap for bracket 60x60 black (3842548853)
Weight	0.16 kg