

Damper DA 2/100-C for TS 2plus Transfer System - Bosch Rexroth 3842525734

Item no. BRR-3842525734

Manufacturer Bosch Rexroth

The DA 2/100-C damper brakes and separates the WT 2 and WT 2/F workpiece pallets during infeeding on the TS 2plus transfer system. The housing is hard-anodized aluminum with a hardened steel stop. Supplied not assembled, including fastening material.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
HS-Code	84313900
Weight	1.49 kg



DESCRIPTION

The DA 2/100-C damper is part of the transport control of the Bosch Rexroth TS 2plus transfer system. It brakes and stops the WT 2 and WT 2/F workpiece pallets during infeeding, providing a controlled, gentle stop that protects the conveyed material.

- Hard-anodized aluminum housing with a hardened steel stop
- Rated for workpiece pallet total weights up to 100 kg
- Pneumatic connection via straight fitting Ø 6 mm
- Supplied including fastening material

TECHNICAL DATA

Mass [m]	5 kg
Workpiece pallet total weight [mG]	100 kg
Nominal speed	6, 9, 12, 15, 18 m/min
Max. total weight per speed	100, 100, 100, 95, 55 kg
Operating temperature max.	0 ... +60 °C
Pneumatic straight connection Ø	6 mm
Housing	Aluminum, hard anodized
Stop	Steel, hardened

Scope of delivery	Incl. fastening material
Delivery information	Not assembled
Notice	High-temperature damper on request
Weight	1.49 kg