

Leveling foot D30, M12x72.5, ESD, galvanized steel, slot 8/10 - Bosch Rexroth 3842529025

Item no. BRR-3842529025

Manufacturer Bosch Rexroth

ESD-capable leveling foot for aligning and leveling aluminum profile frames. The 14 mm adjustment range compensates for uneven floors, while the conductive design dissipates electrostatic charges. Suits profiles with slot 8 and slot 10.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	China
HS-Code	73181595
Lenght	72,5 mm
Weight	0.095 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Bosch Rexroth D30 leveling foot is used to align and level aluminum profile structures, machine frames and workstations. The ESD version dissipates electrostatic charges and is suitable for work areas in electronics production.

- ESD-capable for dissipation of electrostatic charges
- 14 mm adjustment range to compensate for uneven floors
- load capacity up to 8000 N
- suitable for profiles with slot 8 and slot 10
- M12 thread in galvanized steel

TECHNICAL DATA

Profile slot	8, 10
ESD	yes
Thread size	M12
Diameter D	30 mm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Length L	72.5 mm
Adjustment range V	14 mm
Force F	8000 N
Material	Steel, galvanized
Packaging unit	20 pcs
Weight	0.095 kg
Recommended accessories	bearing ring when cover caps with a hole are used