

T-slot nut 8, M8, swivel-in with spring retention, ESD, steel galvanized - Bosch Rexroth 3842529297

Item no. BRR-3842529297

Manufacturer Bosch Rexroth

Swivel-in T-slot nut for profile slot 8 with M8 thread and ESD properties. A stainless spring holds the nut at any point along the slot so it cannot fall out before being screwed down. For retrofit fastenings on aluminium profiles.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	China
HS-Code	73181692
Weight	0.0042 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The swivel-in T-slot nut from Bosch Rexroth is used for retrofit fastening of add-on parts in profile slot 8 of aluminium profiles. It is swivelled into the slot and held at the required position by an integrated stainless spring.

- Swivel-in design, positionable anywhere along the slot
- Spring retention prevents the nut from falling out before fastening
- ESD-capable for electrostatically protected areas
- Groove retention up to 2200 N

TECHNICAL DATA

Profile slot	8
Thread size	M8
Swivel-in	yes
ESD	yes
Length l	16 mm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Dimension h	4.8 mm
Dimension h1	1 mm
Groove retention Fmax	2200 N
Material	Steel, galvanized
Material information	Steel, galvanized; spring: spring steel, stainless
Packaging unit	100 pcs
Weight	0.0042 kg