

T-slot nut 10 M5, swivel-in, ESD, steel galvanized - Bosch Rexroth 3842529298

Item no. BRR-3842529298

Manufacturer Bosch Rexroth

Swivel-in T-slot nut with M5 thread for profile slot 10. The spring-loaded design holds the nut in place and allows retrofitting into closed profile frames at any point. ESD-capable for use in electrostatic protected areas.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

HS-Code **73181692**

Weight **0.00882 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The swivel-in T-slot nut 10 M5 from Bosch Rexroth is used to fasten add-on components to aluminium profiles with slot 10. Thanks to its spring-loaded design it can be inserted into a closed profile at any position afterwards and automatically holds its place.

- Swivel-in - retrofit mounting without access to the profile end
- Stainless spring steel spring keeps the nut in position
- ESD-capable for electrostatic protected areas
- High groove retention up to 18000 N

TECHNICAL DATA

Profile slot	10
Thread size	M5
Swivel-in	yes
ESD	yes
Length l	20 mm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Dimension h	5.3 mm
Dimension h1	1.5 mm
Min. groove retention Fmin	8000 N
Max. groove retention Fmax	18000 N
Material	Steel, galvanized
Spring	Spring steel, stainless
Packaging unit	100 pcs
Weight	0.00882 kg