

Strut Profile 15x120, Slot 8, Anodized Aluminum, Length 3000 mm - Bosch Rexroth 3842537821

Item no. BRR-3842537821

Manufacturer Bosch Rexroth

Standard 15x120 strut profile in anodized aluminum with profile slot 8 and a 30 mm modular dimension. Its high stiffness in the x-direction suits load-bearing frames and structures in machine and plant engineering. Supplied as a packaging unit of 10 profiles, each 3000 mm.

TECHNICAL DATA

Country of Manufacture	Germany
HS-Code	76042100
Length	3000 mm
Note	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Weight	83 kg



DESCRIPTION

The Bosch Rexroth 15x120 strut profile is a standard profile made of anodized aluminum with profile slot 8 and a 30 mm modular dimension. It is intended for design engineers in machine and plant engineering who build stable frames, racks and load-bearing structures.

- High area moment of inertia in the x-direction for load-bearing applications
- 9 open slot 8 grooves for flexible connection of brackets and accessories
- Anodized surface for corrosion protection and a uniform appearance

TECHNICAL DATA

Condition on delivery	Packaging unit in standard length
Cross-section	15x120
Profile slot	8
Open slots	9
Modular dimension	30 mm
Profile type	Standard
Length [L]	3000 mm
Color	Natural
Material	Aluminum, anodized

Area moment of inertia in x-direction [Ix]	110.4 cm ⁴
Moment of resistance in x-direction [Wx]	18.4 cm ³
Area moment of inertia in y-direction [Iy]	2.2 cm ⁴
Moment of resistance in y-direction [Wy]	2.7 cm ³
Profile surface [A]	9 cm ²
Mass [m]	2.4 kg
Delivery unit	10
Weight (packaging unit)	83 kg
Recommended accessories	Cover cap 15x120, signal gray or black