

Swivel mounting 180°, galvanized steel, slot 8/10, ESD - Bosch Rexroth 3842538275

Item no. BRR-3842538275

Manufacturer Bosch Rexroth

Articulated swivel mounting for joining aluminum profiles with a continuous 180° swivel range. Galvanized steel, ESD-capable and suited to profile slot 8 and 10. The set position is locked tool-free with the clamping lever.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Germany
HS-Code	83024900
Norm	DIN 125, DIN 9021-8, ISO 4762
Weight	0.408 kg



20217

STANDARDS & COMPLIANCE

ESD safe ISO4762

DESCRIPTION

The swivel mounting 180° joins two aluminum profiles in an articulated way and allows continuous pivoting over 180°. It is suited to building workstations and material levels in manual production systems.

- 180° swivel range for flexible alignment of attached components
- Clamping lever with disk locks the set position without tools
- ESD-capable for use in electrostatically protected areas
- Joins profile slot 8 to slot 8 or slot 10 (P1/P2: 8/8, 8/10)

TECHNICAL DATA

Profile slot	8; 10
Profile slot P1/P2	8/8, 8/10
ESD	yes
Material	Steel, galvanized

Material information	Swivel mounting: steel, galvanized; clamping lever: diecast zinc, black plastic coated
Scope of delivery	Incl. fastening material (FS), clamping lever with disk and swivel-in sliding block with spring
Fastening material	1x cylinder head screw ISO4762-M8x12, 2x sliding block groove 8 M8 suspended, 2x cylinder head screw ISO4762-M6x16, 2x T-nut groove 10 M6, 2x cylinder head screw ISO4762-M6x12, 1x T-nut groove 8 M6, 2x washer DIN125-A6,4, 1x washer DIN9021-8,4
Packaging unit	1
Weight	0.408 kg