

Strut Profile 40x120x120L, ESD, Anodized Aluminum, Slot 10 - Bosch Rexroth 3842538287

Item no. BRR-3842538287

Manufacturer Bosch Rexroth

Angled strut profile 40x120x120L made of anodized aluminum with profile slot 10 for the modular construction of frames and machine bases. ESD-capable and therefore suitable for electrostatically protected areas. Supplied as a packaging unit of 4 profiles, 6070 mm each.

TECHNICAL DATA

Country of Manufacture	Sweden
HS-Code	76042100
Length	6070 mm
Note	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Weight	175 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The angled strut profile 40x120x120L from Bosch Rexroth is a load-bearing basic element made of anodized aluminum for building frames, machine bases and support structures. With profile slot 10 and a 40 mm modular dimension, it integrates flexibly into the profile construction system.

- Angled L-geometry 40x120x120 for rigid, bending-resistant structures
- ESD-capable for use in electrostatically protected areas
- Anodized natural surface, corrosion-resistant and low-maintenance
- Supplied as a packaging unit of 4 profiles, 6070 mm each

TECHNICAL DATA

Cross-section	40x120x120L
Dimensions	40x120x120
Profile type	angled
Modular dimension	40 mm
Profile slot	10

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Open slots	12
ESD	yes
Color	Natural
Material	Aluminum, anodized
Length [L]	6070 mm
Delivery unit	4 profiles
Condition on delivery	Packaging unit in standard length
Profile surface [A]	24.6 cm ²
Area moment of inertia [Ix]	318 cm ⁴
Area moment of inertia [Iy]	318 cm ⁴
Moment of resistance [Wx]	42.2 cm ³
Moment of resistance [Wy]	42.2 cm ³
Torsional moment of inertia [It]	37.1 cm ⁴
Moment of torsion resistance [Wt]	19 cm ³
Mass [m]	6.7 kg/m
Weight	175 kg
Recommended accessories	Cover cap 40x40 and 40x80, signal gray or black