

Tensioning connector SV 10L, ESD, galvanized steel, slot 10 - Bosch Rexroth 3842538491

Item no. BRR-3842538491

Manufacturer Bosch Rexroth

The SV 10L tensioning connector joins aluminium profiles with a force-fit butt joint via profile slot 10, creating a stable connection that is almost invisible from the outside. It is ESD-capable and suited to profiles 45x...L, 45x90SL and 90x90SL. Typically used in machine and fixture construction.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	China
HS-Code	83024900
Weight	0.048 kg



18663

STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The SV 10L tensioning connector creates a force-fit butt joint between aluminium profiles. It is inserted into profile slot 10 and tightened with the tensioning screw, producing a stable connection that is almost invisible from the outside. Suitable for machine, frame and fixture construction.

- Force-fit butt joint with no visible connecting elements on the profile surface
- ESD-capable for use in electrostatically protected areas
- Steel, galvanized - corrosion-protected and high load capacity
- For profiles 45x...L, 45x90SL and 90x90SL with slot 10

TECHNICAL DATA

Profile slot	10
ESD	yes
Profile [P]	45x...L, 45x90SL, 90x90SL
Bending moment 1	110 Nm
Torsional moment	30 Nm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Material
Packaging unit
Weight

Steel, galvanized

10

0.048 kg