

Belt GT 2/A, L=250 m, PA, ESD, for TS 2plus Transfer System - Bosch Rexroth 3842539479

Item no. BRR-3842539479

Manufacturer Bosch Rexroth

Flat belt GT 2/A made of polyamide (PA), supplied as a 250 m roll for longitudinal transport in the Bosch Rexroth TS 2plus transfer system. The conductive ESD version suits electrostatically protected areas. A belt mounting tool kit and glue are required for assembly.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Switzerland
HS-Code	39269097
Weight	13.5 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The GT 2/A belt is a conductive flat belt made of polyamide (PA) for longitudinal transport in the Bosch Rexroth TS 2plus transfer system. It is supplied as continuous stock on a 250 m roll and is aimed at system integrators and maintenance teams building new section units or replacing worn belts.

- ESD-capable for use in electrostatically protected areas
- Polyamide (PA) material for continuous operation in longitudinal transport
- 250 m roll for cutting to length across multiple section units

A belt mounting tool kit and glue are required for assembly (not included in delivery).

TECHNICAL DATA

ESD	yes
Material	PA (polyamide)
Length L	250000 mm (250 m)

Required accessories**Weight**

Belt mounting tool kit, glue

13.5 kg