

T-Slot Nut 6, M4, Steel Galvanized, ESD - Bosch Rexroth 3842542692

Item no. BRR-3842542692

Manufacturer Bosch Rexroth

T-slot nut for profile slot 6 with M4 thread, made of galvanized steel and ESD-capable. It provides a groove retention force of up to 3000 N for secure bolted connections. The matching spring is required to fix it in the slot.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **China**

HS-Code **73181692**

Weight **0.0031 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The T-slot nut 6 M4 is used to add fastening points retrospectively in the profile slot 6 of Bosch Rexroth aluminum profiles. It is intended for machine and fixture building where bolting points need to be placed flexibly.

- Made of galvanized steel for high load capacity
- Groove retention up to 3000 N for secure connections
- ESD-capable for applications with discharge requirements

TECHNICAL DATA

Profile slot	6
Thread size	M4
Length l	12 mm
Dimension h	4 mm
Dimension h1	1 mm
Groove retention Fmax	3000 N

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Material
ESD
Required accessories
Packaging unit
Weight

Steel, galvanized
yes
Spring
100
0.0031 kg