

Swivel-in T-slot nut 8 M8, stainless steel, ESD - Bosch Rexroth 3842547821

Item no. BRR-3842547821

Manufacturer Bosch Rexroth

Swivel-in T-slot nut for profile slot 8 with M8 thread for adding fixings to aluminium profiles after assembly. Made of stainless steel, ESD-capable, with a groove retention force of up to 2200 N.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Germany
HS-Code	73181639
Weight	0.0047 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The swivel-in T-slot nut for profile slot 8 is used to fasten components to aluminium profiles after assembly, without having to open the end of the profile. It is placed into the slot and locked in position by turning. The ESD version in stainless steel is suitable for areas with electrostatic protection.

- Swivel-in design for retrofitting into closed profiles
- M8 internal thread for secure bolted connections
- High groove retention force up to 2200 N
- Stainless steel, spring in stainless spring steel, ESD-capable

TECHNICAL DATA

Attribute		Value
Profile slot	8	
ESD	yes	
Swivel-in	yes	

Attribute	Value
Thread size	M8
Length l	16 mm
Dimension h	4.8 mm
Dimension h1	1 mm
Groove retention Fmax	2200 N
Material	stainless steel, spring: stainless spring steel
Packaging unit	100 pcs
Weight	0.0047 kg