

Suspension Profile 15x30 ESD, Natural Aluminium, 50-3000 mm - Bosch Rexroth 3842993063

Item no. BRR-3842993063

Manufacturer Bosch Rexroth

ESD-compliant suspension profile in aluminium (15x30 mm, profile slot 8) for tool and parts presentation at manual assembly workstations. Supplied in variable lengths from 50 to 3000 mm, cut to size on request. Fixing requires a screw and T-nut.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Germany
HS-Code	76042100
Note	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Weight	0.013 kg



20242

STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Bosch Rexroth 15x30 ESD suspension profile extends the aluminium profile system for manual production lines with an ESD-safe hanging solution - designed for tool and parts supply at electrostatically protected workstations. The profile is supplied in variable lengths from 50 to 3000 mm and can be cut to the required dimension.

- ESD-compliant: protects sensitive assemblies against electrostatic discharge
- Variable length 50-3000 mm: precise cut-to-size for each workstation layout
- Profile slot 8: compatible with the Bosch Rexroth aluminium profile system
- Natural aluminium: lightweight, corrosion-resistant, dimensionally stable
- Required accessories: screw and T-nut (sold separately)

TECHNICAL DATA

Attribute	Value
Dimensions	15 x 30 mm
Length min. [L min]	50 mm
Length max. [L max]	3000 mm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Attribute	Value
Condition on delivery	Variable length
Delivery unit	1
Material	Aluminum
Color	Natural
ESD	Yes
Profile slot	8
Profile surface [A]	2 cm ²
Mass [m]	0.6 kg/m
Area moment of inertia X [Ix]	2 cm ⁴
Moment of resistance X [Wx]	2.7 cm ³
Area moment of inertia Y [Iy]	0.5 cm ⁴
Moment of resistance Y [Wy]	0.3 cm ³
Required accessories	Screw, T-nut