

Strut Profile 11x20, Anodized Aluminum, Slot 8, 1 Open Slot - Bosch Rexroth 3842993688

Item no. BRR-3842993688

Manufacturer Bosch Rexroth

Compact aluminum strut profile with an 11x20 mm cross-section and one open slot 8 for space-saving integration in assembly frames and support structures. Anodized natural finish, available cut-to-length from 50 to 2000 mm. Modular dimension 30 mm, fully compatible with the Bosch Rexroth profile system.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
HS-Code	76042100
Note	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Weight	0.1 kg



DESCRIPTION

The Bosch Rexroth strut profile 11x20 is an anodized aluminum profile designed for slim load-bearing structures, guards, and assembly fixtures where installation space is restricted. Its single open slot 8 and 30 mm modular dimension integrate directly into the modular Bosch Rexroth profile system.

- Compact 11x20 mm cross-section - minimal footprint with reliable structural connection
- Anodized aluminum - corrosion-resistant surface, ready to install without further treatment
- Cut-to-length flexibility - any length from 50 to 2000 mm on request
- Standard finishing D7.8 / D11 available - direct assembly without additional machining
- Recommended accessories: cover cap 11x20 in black or signal gray

TECHNICAL DATA

Property	Value
Cross-section	11x20 mm
Profile slot	8
Modular dimension	30 mm
Open slots	1
Profile type	Standard

Property	Value
Color	Natural
Material	Aluminum, anodized
Length min.	50 mm
Length max.	2000 mm
Mass	0.3 kg/m
Profile surface (A)	1 cm ²
Area moment of inertia I _x	0.5 cm ⁴
Area moment of inertia I _y	0.1 cm ⁴
Moment of resistance W _x	0.7 cm ³
Moment of resistance W _y	0.3 cm ³
Standard finishing	D7.8 / D11
Packaging unit	1