

Lean Conveyor Track with Rail Holder, Multi-Color Rollers - Bosch Rexroth 3842998382

Item no. BRR-3842998382

Manufacturer Bosch Rexroth

Configurable aluminum U-profile conveyor track for Lean assembly lines, supplied fully assembled as a matched pair (right and left sections) with rail holders for direct suspension on tubular cross ties. Up to three roller colors (black, red, yellow, green) support Kanban visualization or good/reject part identification. Available with or without lateral guide and as an ESD-conductive version.

TECHNICAL DATA

Country of Manufacture **Germany**

HS-Code **84283990**

Weight **0.15 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Lean conveyor track with rail holder is a configurable aluminum U-profile system designed for Lean production and assembly environments. Rail holders allow direct suspension on tubular cross ties without additional brackets. Each unit ships fully assembled as a pair of conveyor sections - right and left.

- Multi-color roller loading (up to three colors: black, red, yellow, green) for Kanban visualization or good/reject separation
- Choice of conveyor media: rollers Ø 32 mm with or without roller flange at various spacings; roller elements (RE45, RE45SK); or slide rails with or without integrated lateral guide (GS, GSSK)
- Lateral guide optional (SF): with or without roller flange guide
- Rail holder version (S): with or without integrated stop
- Available as ESD-conductive version (U-profile: aluminum plain)
- Gradient adjustable from 0 to 10 %, recommended setting 6 %

TECHNICAL DATA

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Parameter	Value
Material	Aluminum profile
Conveyor medium (FM)	Rollers Ø 32 mm with/without roller flange, various spacing
Roller colors F1 / F2 / F3	Black, red, yellow, green (max. 160 rollers per color)
Horizontal distance between tubular cross ties (TM)	355 to 6000 mm
Gradient (G)	0 to 10 % (recommended: 6 %)
Lateral guide (SF)	With / without
Rail holder version (S)	With / without stop
Conductivity (ESD)	Yes / no
Scope of delivery	Conveyor track consisting of two sections (right/left) with rail holders
Delivery	Fully assembled