

Workpiece Pallet WT 2/H 12.7 mm for Transfer System TS 2plus, ESD-Suitable - Bosch Rexroth 3842998751

Item no. BRR-3842998751

Manufacturer Bosch Rexroth

Aluminum workpiece pallet for the TS 2plus transfer system with a 12.7 mm carrying plate, covering 17 standard sizes from 400 x 400 mm to 1200 x 1200 mm. PE wear pads and integrated stop dampers ensure quiet, low-wear operation. Available fully assembled (MT 1) or as a self-assembly kit (MT 0), ESD-suitable.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
HS-Code	84662020
Weight	0.0099 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The WT 2/H 12.7 workpiece pallet carries and transports parts within the TS 2plus transfer system, supporting combined workpiece weights of up to 240 kg. The universal aluminum carrying plate - 12.7 mm thick - is available in 17 standard sizes (bWT x lWT = 400 x 400 mm to 1200 x 1200 mm); special dimensions are available on request. PE wear pads on the corner modules and sliders keep running noise and wear to a minimum, while integrated stop dampers absorb the impact when pallets accumulate behind one another. Certified for use in electrostatic protected areas (EPA).

- 12.7 mm carrying plate thickness - fits the full TS 2plus product range
- PE wear pads on corner modules and sliders for quiet, low-wear operation
- Integrated stop dampers for smooth pallet accumulation without impact
- 17 standard sizes, square and rectangular combinations from 400 mm to 1200 mm
- Supplied fully assembled (MT = 1) or as a kit for self-assembly (MT = 0)
- ESD-suitable for use in EPA environments

TECHNICAL DATA

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Parameter	Value
Carrying plate thickness dPL	12.7 mm
Carrying plate material	Aluminum
Corner modules / sliders	PE (polyethylene)
Max. workpiece pallet total weight mG	240 kg
Workpiece pallet width bWT	400 / 480 / 640 / 800 / 1040 / 1200 mm
Workpiece pallet length IWT	400 / 480 / 640 / 800 / 1040 / 1200 mm
Number of standard sizes	17
ESD-suitable	Yes
Delivery state	Assembled (MT = 1) or kit, not assembled (MT = 0)
Scope of delivery	Carrying plate, corner modules, wear pads, damping elements
Recommended accessory	2x positioning bushing kit WT 2/H LE 2 (required when using PE 2/H positioning unit)
Weight (catalog entry)	0.0099 kg (varies by size)