

WT 2/H Workpiece Pallet Kit without Carrying Plate, ESD-Suitable - Bosch Rexroth 3842998756

Item no. BRR-3842998756

Manufacturer Bosch Rexroth

Self-assembly kit for WT 2/H workpiece pallets, supplied without carrying plate and unassembled - available in 17 standard sizes from 400 x 400 mm to 1200 x 1200 mm. PE wear pads ensure quiet, low-wear operation; integrated stop dampers prevent hard contact with adjacent pallets. Suitable for use in electrostatic protected areas (EPA).

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
HS-Code	84313900
Weight	0.0099 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The WT 2/H workpiece pallet kit allows custom configuration of workpiece pallets through self-assembly - delivered without carrying plate and unassembled. It covers 17 standard sizes from 400 x 400 mm to 1200 x 1200 mm, and can be combined with various carrying plates, positioning bushings, and fastening elements to meet specific application requirements. Special dimensions are available on request.

- PE wear pads for quiet operation and low wear
- Integrated stop dampers for smooth, low-impact running onto adjacent pallets
- ESD-suitable for use in electrostatic protected areas (EPA)
- 17 standard sizes; special dimensions on request
- Compatible with carrying plates, positioning bushings, and fastening elements from the WT 2/H range

TECHNICAL DATA

Specification	Value
Delivery condition	Parts kit without carrying plate, not assembled

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Specification	Value
Workpiece pallet width bWT	400 / 480 / 640 / 800 / 1040 / 1200 mm
Workpiece pallet length lWT	400 / 480 / 640 / 800 / 1040 / 1200 mm
Workpiece pallet total weight mG	240 kg (max.)
Wear pad material	PE (polyethylene)
ESD-suitable	Yes
Scope of delivery	Corner modules, sliders with PE wear pads, damping elements
Recommended accessories	2x positioning bushing kit WT 2/H LE 2 (required when using a PE 2/H positioning unit)