

ESD floor covering Safe-STAT, light grey, rubber 2.5 mm, roll 1.90 x 10 m - A1-ESD C-204-33216

Item no. C-204 33216

Manufacturer A1-ESD

Dissipative ESD floor covering Safe-STAT in two-layer synthetic rubber, light grey. 2.5 mm thick, 1.90 x 10.00 m roll, resistance approx. 10^7 ohms, loose-lay or bonded.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Light Grey
ESD equipment	ESD-Beläge
Norm	IEC 61340-5-1
Sales unit	Rolle 1,90 x 10 m
Weight	65 kg
Width	1900



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Safe-STAT ESD floor covering drains electrostatic charges reliably to ground and protects sensitive components inside the EPA. The two-layer synthetic rubber can be loose-laid thanks to its low-resistance backing, or bonded.

BENEFITS

- Defined resistance of approx. 10^7 ohms
- Two-layer synthetic rubber with high durability
- Loose-lay or bonded installation, wide 1.90 m web

TECHNICAL DATA

- Material: synthetic rubber, two-layer
- Colour: light grey
- Thickness: 2.5 mm
- Dimensions: 1.90 m x 10.00 m (roll)
- Resistance: approx. 10^7 ohms
- Installation: loose-lay or bonded

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

APPLICATIONS

Suitable for manufacturing, assembly and test areas in the electronics industry that require a dissipative floor.

STANDARDS AND COMPLIANCE

Supports EPA concepts for ESD protection to IEC 61340-5-1.