

ESD pallet 120 x 80 x 15.5 cm - Auer ESD H 1208 OS

Item no. ESD H 1208 OS

Manufacturer Auer

ESD pallet in electrically conductive HDPE in the 120 x 80 cm format for the safe storage and transport of electronic components. The electrically conductive material protects sensitive electronics from electrostatic discharge.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Germany
HS-Code	39239000
Note	Stück auf Palette - 15
Weight	16.77 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

ESD pallet in electrically conductive HDPE in the 120 x 80 cm format for the safe storage and transport of electronic components.

- The electrically conductive material protects sensitive electronics from electrostatic discharge.
- Low tare weight with high load capacity, just like the light pallet.
- Empty pallets nest space-savingly inside one another.
- Available with or without a retaining edge.
- Dissipative design to IEC 61340-5-1, volume resistance $10^3 < 10^{10}$ Ohm/cm for safe handling of electrostatic discharge sensitive components.

Used in electronics manufacturing, EMS and semiconductor logistics for ESD-protected transport.

Made of electrically conductive HDPE, manufactured in Germany.

Technical data

Outer dimensions L x W x H 120 x 80 x 15.5 cm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Upper surface	Closed
Non-continuous retaining edge	without retaining edge
Weight	16.77 kg
Loading capacities	Dynamic: 1.500 kg / Static: 3.500 kg / High rack: 300 kg
Bending ±	15 mm
Tolerance ±	10%
Material	ESD PP
Colour	traffic black similar RAL 9017
Special volume resistance	$10^3 < 10^{10}$ Ohm/cm