

Dual conductor coil cord, straight mono plug, 3 m - Desco 2370

Item no. DESCO 2370

Manufacturer Desco

Dual conductor coil cord for personal grounding with a 1 megohm safety resistor. Straight 3.4 mm mono plug for SCS dual-wire wristbands and continuous monitors, 3 m, made in the USA.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85331000
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.03 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

This dual conductor coil cord connects a dual-wire wrist strap to a continuous monitor. If one conductor is damaged, the path-to-ground is maintained through the second conductor, so personal grounding stays intact. At 3 m it gives extra reach at the workstation.

BENEFITS

- Two conductors: if one is damaged, grounding is kept through the other
- Integrated 1 megohm safety resistor to protect against accidental contact with line voltage
- Reinforced strain relief at the resistor connection, tested to over 200,000 bending cycles (ANSI/ESD S1.1, requirement 16,000)

TECHNICAL DATA

- Length: 3 m
- Plug: straight 3.4 mm mono plug
- Safety resistor: 1 megohm
- For SCS dual-wire wristbands and dual-wire monitors (not included)
- Origin: USA

- Selling unit: 1 piece

Part of a personal grounding system per IEC 61340-5-1; tested to ANSI/ESD S1.1.