

Desco 237215. Conductive PCB Rack, 175mmx500mm


Item no. DESCO 237215

Manufacturer Desco

DESCO 237215. Conductive PCB Rack, 175mm x 500mm

TECHNICAL DATA

Ausführungsklasse	TEC
Certification	IEC 61340-5-1
HS-Code	39231090
Weight	0.699 kg



STANDARDS & COMPLIANCE

ESD safe EN 61340-5-1

DESCRIPTION

- Moulded from a carbon black-filled polypropylene compound.
- Designed to protect CMOS loaded boards in storage.
- Recommended maximum operating temperature is 85°C.
- Open carrying handles.
- Measurements: 175mm x 500mm.
- Weight: 0.7kg.
- 20 slots with easy-to-load angle: 3mm x 8mm on a 15mm pitch
- Recyclable

"Tools intended for use within the EPA [ESD protected area] shall, as far as is practicable, be so constructed that they do not generate or hold an electrostatic charge

All tools and machinery, for example electrical, mechanical or pneumatic, shall be so constructed that any non-insulating part of the tool or machine which may touch an ESDS [ESD sensitive items] shall be at EPA ground potential." [EN 61340-5-1 clause 5.2.10 Tools, machinery, dispensers and test equipment]

Technical information

- - Conductive PCB Rack, 175mm x 500mm