

Compact Cylinder ADN-100-15-I-P-A - Festo 536385

Item no. FES-536385

Manufacturer Festo

EAN 4052568171735

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Ausführungstyp	einseitige Kolbenstange
Betriebsdruck max [bar]	10.000000
Bohrung (mm)	100.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Cushioning	P: Elastic silencer rings / plates double-sided
Dichtmaterial	TPE-U(PU)
Funktion	doppeltwirkend
HS-Code	84123100
Hub [mm]	15.000000
Medium	Druckluft
Mounting position	arbitrary
Norm	ISO 21287
Pneumatischer Anschluss	G1/8
Position sensing	Yes
Serie	ADN
Temperature (max.)	80
Weight	1.8 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	15
Piston diameter	100 mm
Piston rod thread	M12
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Complies to standard	ISO 21287
Piston rod end	Female thread

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Position detection	For proximity switch
Variants	One-sided piston rod
Operating pressure [bar]	0.6 to 10
Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	2,50
Theoretical force at 6 bar, Return flow [N]	4.524
Theoretical force at 6 bar, flow [N]	4.712
Moving mass at 0 mm stroke [g]	570
Weight supplement per 10 mm stroke [g]	98
Base weight at 0 mm stroke [g]	2.154
Supplement moved mass per 10 mm stroke [g]	25
Fastening type	With throughway bores With female thread With Accessories Selectively:
Pneumatic connection	G1/8
Material information	RoHs compliant
Cover material	Aluminium die casting Coated
Seals material	TPE-U(PUR)
Piston rod material	High-alloyed steel
Cylinder tube material	Aluminium wrought alloy Smooth anodised