

Compact Cylinder ADN-40-20-A-P-A - Festo 536292

Item no. FES-536292

Manufacturer Festo

EAN 4052568171001

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Ausführungstyp	einseitige Kolbenstange
Betriebsdruck max [bar]	10.000000
Bore (mm)	40.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Cushioning	P: Elastic silencer rings / plates double-sided
Dichtmaterial	TPE-U(PU)
Funktion	double-acting
HS-Code	84123100
Hub [mm]	20
Medium	Compressed air
Mounting position	arbitrary
Norm	ISO 21287
Operating conditions	ISO 8573-1
Pneumatic connection	G1/8
Position sensing	Yes
Series	ADN
Temperature (max.)	80
Weight	0.42 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	20
Piston diameter	40 mm
Piston rod thread	M10x1,25
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Complies to standard	ISO 21287

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston rod end	Male thread
Position detection	For proximity switch
Variants	One-sided piston rod
Operating pressure [bar]	0.6 to 10
Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	0,70
Theoretical force at 6 bar, Return flow [N]	686
Theoretical force at 6 bar, flow [N]	754
Moving mass at 0 mm stroke [g]	80
Weight supplement per 10 mm stroke [g]	37
Base weight at 0 mm stroke [g]	346
Supplement moved mass per 10 mm stroke [g]	9
Fastening type	With throughway bores With female thread With Accessories Selectively:
Pneumatic connection	G1/8
Material information	RoHs compliant
Cover material	aluminium anodized
Seals material	TPE-U(PUR)
Piston rod material	High-alloyed steel
Cylinder tube material	Aluminium wrought alloy Smooth anodised