

Standards-Based Cylind ESNU-16-10-P-A - Festo 19263

Item no.	FES-19263	Manufacturer	Festo
Manufacturer no.	ESNU-16-10-P-A	EAN	4052568003524

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Article authenticity	Original product
Betriebsdruck max [bar]	10.000000
Bohrung (mm)	16.000000
Condition of article	New
HS-Code	84123100
Hub [mm]	10.000000
Pneumatischer Anschluss	M5
Weight	0.09 kg



STANDARDS & COMPLIANCE

ISO 6432 ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	10
Piston diameter	16 mm
Piston rod thread	M6
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Complies to standard	CETOP RP 52 P ISO 6432
Piston rod end	Male thread
Construction set up	Piston piston rod cylinder tube
Position detection	For proximity switch

Variants	One-sided piston rod
Operating pressure [bar]	1.2 to 10
Principle of operation	Pressing single action
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	0,15
Theoretical force at 6 bar, flow [N]	106,5
Moving mass at 0 mm stroke [g]	23,0
Weight supplement per 10 mm stroke [g]	4,6
Base weight at 0 mm stroke [g]	89,9
Supplement moved mass per 10 mm stroke [g]	2
Fastening type	With Accessories
Pneumatic connection	M5
Material information	RoHs compliant
Cover material	Aluminium wrought alloy No-colour anodised
Seals material	NBR TPE-U(PU)
Piston rod material	High-alloyed stainless steels
Cylinder tube material	High-alloyed stainless steels