

Guide Unit FENG-63-100-KF - Festo 34514

Item no. FES-34514


Manufacturer Festo

EAN 4052568009953

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code	84821090
Hub [mm]	100.000000
Weight	5 kg
Werkstoff	Aluminium



DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

size	63
Stroke [mm]	100
installation position	arbitrary
Guide	ball guide
Construction set up	Guide
ambient temperature [°C]	-20 to 80
Max. force Fy [N]	1.260
Max. force Fy static [N]	1.600
Max. force Fz [N]	1.260
Max. force Fz static [N]	1.600
Max. torque Mx [Nm]	75
Max. torque Mx static [Nm]	95
Max. torque My [Nm]	90
Max. torque My static [Nm]	115

Max. torque Mz [Nm]	90
Max. torque Mz static [Nm]	115
Pushing force [N]	15
Product weight [g]	5.900
Fastening type	with female thread
Material information	Copper and PTFE-free RoHs compliant
Guide element material	Quenched and tempered steel
Housing material	Aluminium wrought alloy, anodised
Joch plate material	Aluminium wrought alloy, anodised